



## 145000 ScriptTag HD

ScriptTag HD is a 2.45 GHz Read/Write heavy duty ID-tag. The tag is specially designed for tough environments and high/low temperatures and is the standard choice for applications where there is a need to write information to the ID-tag. TagMaster's heavy duty ID-tags are vibration resistant, waterproof, UV stable, corrosion- and chemical resistant.

### KEY FEATURES

- Long read-range
- Lifetime of 6 to 10 years
- Heavy-duty design for tough environments
- Small size
- Unique identity, cannot be changed or copied
- Environmentally harmless
- 32 bit ID checksum for elimination of substitution errors
- Fast reading – no wake-up time
- Easy to mount on any surface (including metal) with M4 screws, rivets or adhesive tape)
- Low radio emission – license-free

Technical specification: 145000 ScriptTag HD		* Depends on reader type, settings and mounting.
Operating frequency	2.435 GHz to 2.465 GHz	
Reading range*	Example: Up to 6 metres with LR-6HD reader.	
Dimensions	90x58x8 mm / (3.4x2.8x0.3 inch)	
Weight	60 g / (0.13 lb)	
Cover case	Polymer	
Colour	Black	
Battery lifetime	6 to 10 years	
Operating temperature	-40 °C (-40 °F) to +85 °C (+185 °F)	
Encapsulation	IP 67	
Certified to	<b>CE 0413</b> 	CE Certificate according to R&TTE-Directive 1999/5/EC, Annex IV, Health: 1999/519/EC, El.Safety: EN 60950, EMC: EN 301489-3:2000, Radio: EN 300 440:2001, Radio safety: EN 60215, Vibration: IEC 60068-2-64, Shock: IEC 60068-2-27

\* For detailed information please see the 145000 Data Sheet, available on <http://www.tagmaster.com>